


Product News



CAT Pumps New Triplex Plunger Pump Delivers 75 GPM

Our 60-Frame triplex plunger pumps have now expanded to 75 gpm. The new 75 gpm performance is available in three models to cover a variety of industrial liquid applications: 6775 Brass, 6771 Stainless Steel, and 6777 NAB. These new 75 gpm models feature a special guided valve design providing added strength and durability under high flow operation. Custom Features include: Optional Brass, 316SS, or NAB heads for liquid compatibility including fresh water, clean oils, oilfield waste water, and sea water. Optional seals and o-rings providing compatibility and added life with a variety of industrial liquids. Compact footprint and medium weight permit easy installation for stationary and portable systems, offshore, and containerized systems.

Circle 801

Note: Product News submissions should be emailed to chuckp@adpub.com or mailed to Product News, 1000 Nix Rd., Little Rock, AR 72211. Please be sure that your product announcement is accompanied by a photo of the product. 



Nilfisk-ALTO Upgrades Its Neptune 7 Hot Water Series

Nilfisk-ALTO has introduced the implementation of a new flow unloader on the Neptune 7-58X and Neptune 7-66 hot water pressure washer models, the company announced.

Over the past three to four years, the Neptune 7 Series has come with a pressure-trapped unloader and although there are no problems with this unloader, and it does offer certain advantages, the flow-actuated system will help make the product stronger, according to the company. All Nilfisk-ALTO products operate with an automatic start/stop technology, so implementation of a flow-actuated system will almost eliminate problems related to water leaks. It will also ease motor start-ups and prolong the overall lifetime of the motor.

Circle 802



Pressure Pro Introduces New Electric Hot Water Units

The line offers flow rates from 3.0 gpm to 5.0 gpm and pressure ranges of 1500 psi to 3500 psi. All models feature a rugged 1½-in. powder coated steel roll cage frame with lifting hook, ¾-in. cold rolled steel axles, pneumatic tires with steel rims, super efficient schedule 80 coil with 1-piece rigid insulation combustion chamber, stainless steel coil wrap, 9-gal poly diesel tank with fuel filter, EZ access float tank assembly, high pressure chemical metering systems with shut-off and backflow prevention, high limit over temp protection, safety pressure relief valve, and thermo sensor to prevent overheating in bypass mode. All models are powered by reliable Beckett fuel oil burners, Baldor commercial industrial grade electric motors, and feature AR, CAT, and GP V-belt drive pumps. Standard accessories include trigger gun and insulated grip wand assembly with quick connects, 50-ft. high pressure hose assembly with quick connects, and 0-, 15-, 25-, and 40-degree quick connect nozzles.

Circle 803



High Pressure Equipment's New Single and Double Block and Bleed Needle Valves

High Pressure Equipment Company has developed a new line of block and bleed needle valves delivering safe, reliable operation to 20,000 psi. These new needle valves are offered in both single and double block and bleed configurations. Both valve styles have Type 300 stainless steel tee handles with a non-rotating stem design as well as with optional wetted parts and optional O-rings available. The MVBB series is designed for calibration operations by providing controlled flow to high pressure hydraulic and pneumatic systems through both shut-off regulation and diversion. The DBB series is ideal for pressure monitoring and testing, chemical injection, and drain line isolation applications.

Circle 804